



Flat-type Ethernet Switches

	Unmanaged PoE+	Unmanaged
Model	WGS-804HP	WGS-803

Product Image				
Hardware	LCD	-	-	
	10/100/1000BASE-T	8	8	
	1000 mini-GBIC	-	-	
	100BASE-FX	-	-	
	Switch Fabric	16Gbps	16Gbps	
Power	Inputs	Dual 48~56V DC	12~48V DC or 24V AC	
	Connector	3-pin terminal block, DC socket	3-pin terminal block, DC socket	
	Consumption	140 watts	6 watts	
Mechanical	Dimensions (W x D x H)	148 x 25 x 134 mm	148 x 25 x 134 mm	
	Enclosure	IP30 metal	IP30 metal	
	Mounting	DIN-rail, wall-mountable and magnetic wall mount		
Environment	Operating Temperature	-40~75 degrees C	-10~60 degrees C	
	Operating Humidity	5% to 95%RH (non-condensing)	5% to 95%RH (non-condensing)	
Regulatory	Emissions	FCC Class A, CE Class A	FCC Class A, CE Class A	
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)		





Industrial Flat-type Gigabit Router  
Wall-mount Design, Perfect for Public Facilities

PLANET WGR-500 Series, an all-in-one router solution suitable for industrial applications, features 4-port 10/100/1000BASE-T Gigabit Ethernet and 1-port 100/1000BASE-T Gigabit Ethernet. It offers Layer 3 dynamic IP (DHCP Client), static IP, PPPoE, L2TP, PPTP, intelligent Layer 2 and Layer 4 management functions, and user-friendly interface.

Equipped with 4-port 802.3at PoE+ and in-line power interfaces, the WGR-500-4PV and WGR-500-4P centrally manage power supply to PoE IP cameras and PoE sensors at factories. The WGR-500 Series provides firewall to protect IoT devices against networking attack such as denial-of-service (DoS) and emerging malicious traffic before attacks occur. With firewall protection, it prevents IoT network from threats and keeps networking secure. The WGR-500 series is an ideal solution to meet the demand for the following network applications:

- Building/Home automation network
- Internet of things (IoT)
- IP surveillance
- Wireless LAN

	Touch LCD	Managed PoE+		
Model	WGR-500-4PV	WGR-500-4P	WGR-500	

Product Image				
				
Hardware	LCD	2.4" Color TFT Touch Screen	-	-
	10/100/1000BASE-T	5 (4 LAN, 1 WAN)	5 (4 LAN, 1 WAN)	5 (4 LAN, 1 WAN)
	Inputs	Dual 48~56V DC	Dual 48~56V DC	Dual 9~48V DC
	Connector	3-pin terminal block, DC socket	3-pin terminal block, DC socket	2-pin terminal block, DC socket
Mechanical	Dimensions (W x D x H)	180 x 25 x 140 mm	180 x 25 x 140 mm	148 x 24 x 134 mm
	Enclosure	IP30 metal	IP30 metal	IP30 metal
	Mounting	DIN-rail, wall-mountable and magnetic wall mount		
Environment	Operating Temperature	-10~60 degrees C		
	Operating Humidity	5% to 95%RH (non-condensing)		
Regulatory	Emissions	FCC Class A, CE Class A		
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)		
PoE	PoE Standard	802.3at PoE+	802.3at PoE+	-
	PoE Port	4	4	-
	PoE Budget	120 watts	120 watts	-
	PSE Type	End span	End span	-
Protocol	Power Pin Assignment	1/2(+), 3/6(-)	1/2(+), 3/6(-)	-
	VLAN	IEEE 802.1Q VLAN	IEEE 802.1Q VLAN	IEEE 802.1Q VLAN
Management	Interface	Web	Web	Web
	SNMP	v1, v2c	v1, v2c	v1, v2c
	System Log	System log and remote Syslog		



11F, No 96, Minquan Rd., Xindian Dist., New Taipei City 231, Taiwan (R.O.C.)  
Tel: +886-2-2219-9518 Fax: +886-2-2219-9528 E-mail: sales@planet.com.tw  
PLANET reserves the right to change specifications without prior notice. All brand names and trademarks are property of their respective owners. © PLANET Technology Corporation DM-FLAT0120



Ethernet Switch

Gigabit Router

ERPS Ring for MAN Application - **Recovery Time <10ms**

All-Inclusive Industrial Flat-type Ethernet  
Perfect IP Network Deployment for Buildings and Factories



Dual Power Input




Flat Design



DIN-rail Installation



PoE Usage



Fiber Connection



Magnetic Installation



Touch LCD



Front Access



# Flat-type Ethernet Switches



## Security Building Automation Switches

Suitable for buildings where security is strictly to be enforced, PLANET Industrial Wall-mount Managed Switches offer a comprehensive Layer 2 to Layer 4 Access Control List (ACL). The switches can restrict network access by denying packets based on source and destination IP address, TCP/UDP ports or defined typical network applications. The WGS-5225 Series incorporates advanced ITU-T G.8032 ERPS (Ethernet Ring Protection Switching) technology into customer's industrial automation network to enhance system reliability and uptime. With PLANET Industrial Wall-mount Managed Switches, a tightly-controlled network can be easily had in no time.

## FTTX/MAN Application

PLANET Industrial Wall-mount Managed Switches adopt the double tag VLAN (Q-in-Q) technology to provide low cost and easy operation for service providers carrying traffic for multiple customers across their networks. With two dual-speed SFP slots built in, the deployment distance of PLANET Industrial Wall-mount Managed Switches can be extended up to 120 kilometers (single-mode fiber), which provides a high-performance edge service for FTTx solutions.


To build a network solution of FTTH (Fiber to the Home) or FTTC (Fiber to the Curb) for ISPs, and FTTB (Fiber to the Building) for enterprises, the various distances of SFP and BiDi (WDM) transceivers are optional for customers. For security and various applications, the 8 Gigabit ports of PLANET Industrial Wall-mount Managed Switches can be configured with VLAN settings and connected to different units, offices, floors, houses and departments.



## Unique Flat-type Design with Touch LCD Screen or PoE Functions for Efficient Management

To facilitate the network deployment in any space-limited locations like wall enclosure or electric box found in buildings or outdoors, PLANET has the industrial Ethernet switches and wireless AP designed in a compact flat type. The products can be installed by fixed wall mounting, magnetic wall mounting or DIN rail, thereby making its usability more flexible. With the intuitive LCD Touch Screen or PoE Functions including PD alive check, scheduled power recycling, PoE schedule and PoE usage monitoring, PLANET's flat-type switches greatly promotes efficient and timely network management, perfectly suitable for surveillance, wireless and VoIP networks.



Touch LCD			Managed	
Model	WGS-5225-8T2SV	WGS-5225-8P2SV	WGS-4215-8T	WGS-4215-8T2S
Product Image				
Hardware	LCD	2.4" Color TFT Touch Screen		-
	10/100/1000BASE-T	8	8	8
	1000 mini-GBIC	2	2	2
	100BASE-FX	Compatible	Compatible	Compatible
Power	Switch Fabric	20Gbps	20Gbps	20Gbps
	Inputs	12~48V DC or 24V AC	Dual 48~56V DC	12~48V DC or 24V AC
	Connector	3-pin terminal block, DC socket		3-pin terminal block, DC socket
	Consumption	12 watts	251 watts	10 watts
Mechanical	Dimensions (W x D x H)	180 x 25 x 140 mm	180 x 25 x 140 mm	148 x 25 x 134 mm
	Enclosure	IP30 metal	IP30 metal	IP30 metal
	Mounting	DIN-rail, wall-mountable and magnetic wall mount		
Environment	Operating Temperature	-20~70 degrees C	-20~70 degrees C	-40~75 degrees C
	Operating Humidity	5% to 95%RH (non-condensing)		5% to 95%RH (non-condensing)
Regulatory	Emissions	FCC Class A, CE Class A		FCC Class A, CE Class A
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)		
PoE	PoE Standard	-	802.3at PoE+	-
	PoE Port	-	8	-
	PoE Budget	-	240 watts	-
	PSE Type	-	End span	-
	Power Pin Assignment	-	1/2(+), 3/6(-)	-
Protocol	VLAN	IEEE 802.1Q VLAN/Q-in-Q/Private VLAN/Protocol-based VLAN/Voice VLAN/GVRP		
	IGMP Snooping	v2/v3/query	v2/v3/query	v2/v3/query
	Spanning Tree	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s
	Data Redundancy	ERPS Ring RSTP/MSTP		RSTP/MSTP
	QoS	Port-based/802.1P/IP DSCP Policy-based/Voice VLAN		
	Security	802.1x, Static MAC, MAC filter, Port Security and IP Security		
	Traffic Control	In/out rate limit, storm control		
Management	Interface	Web, telnet, SSH and SSL		
	SNMP	v1, v2c, v3 and trap		
	System Log	System log and remote Syslog		

Managed PoE+				
Model	WGS-5225-8P2S	WGS-4215-16P2S	WGS-4215-8P2S	WGS-804HPT
Product Image				
   				
Hardware	LCD	-	-	-
	10/100/1000BASE-T	8	16	8
	1000 mini-GBIC	2	2	-
	100BASE-FX	Compatible	Compatible	Compatible
Power	Switch Fabric	20Gbps	32Gbps	20Gbps
	Inputs	Dual 48~56V DC	Dual 48~56V DC	Dual 48~56V DC
	Connector	3-pin terminal block, DC socket		
	Consumption	250 watts	250 watts	210 watts
Mechanical	Dimensions (W x D x H)	180 x 25 x 140 mm	245 x 25 x 134 mm	178 x 25 x 134 mm
	Enclosure	IP30 metal	IP30 metal	IP30 metal
	Mounting	DIN-rail, wall-mountable and magnetic wall mount		
Environment	Operating Temperature	-40~75 degrees C	-10~60 degrees C	-40~75 degrees C
	Operating Humidity	5% to 95%RH (non-condensing)		5% to 95%RH (non-condensing)
Regulatory	Emissions	FCC Class A, CE Class A		FCC Class A, CE Class A
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)		
PoE	PoE Standard	802.3at PoE+	802.3at PoE+	802.3at PoE+
	PoE Port	8	16	8
	PoE Budget	240 watts	240 watts	240 watts
	PSE Type	End span	End span	End span
	Power Pin Assignment	1/2(+), 3/6(-)	1/2(+), 3/6(-)	1/2(+), 3/6(-)
Protocol	VLAN	IEEE 802.1Q VLAN/Q-in-Q/Private VLAN/Protocol-based VLAN/Voice VLAN/GVRP		
	IGMP Snooping	v2/v3/query	v2/v3/query	v2/v3/query
	Spanning Tree	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s
	Data Redundancy	ERPS Ring < 10ms	RSTP/MSTP	RSTP/MSTP
	QoS	Port-based/802.1P/IP DSCP Policy-based/Voice VLAN		
	Security	802.1x, Static MAC, MAC filter, Port Security and IP Security		
	Traffic Control	In/out rate limit, storm control		
Management	Interface	Web, telnet, SSH and SSL		
	SNMP	v1, v2c, v3 and trap		
	System Log	System log and remote Syslog		